

## What is Once Off?

ONCE OFF is specially made for cleaning ceramic, porcelain and quarry tiles that are difficult to clean. Many of these types of tile have tiny holes or pores in the surface. Dirt collects in these holes and gives the tiles a "grey" appearance. Where ordinary detergents are ineffective on such tiles, ONCE OFF is excellent. Its powerful cleaning and penetrating action draws the soil out of these tiles.

## For Use On...

ONCE OFF may also be used to clean concrete, bluestone, sandstone, terra cotta and clay or concrete pavers. It is ideal for use on floors in shopping centres, toilets, shower rooms, kitchens and carparks. ONCE OFF is designed for use in autoscrubbers, although it may also be used for mopping, scrubbing with single brush rotary machines and pressure washing.

## Technical Data

### Properties



COLOUR – Transparent, colourless liquid.

ODOUR – Practically odourless

pH = 13 – 14

FOAM – Low-medium foam height, suitable for autoscrubbing, manual scrubbing and mopping

## Dangerous Goods Classification

ONCE OFF is a Class 8 corrosive liquid.

U.N. No: 1719	CLASS: 8
PACK GRP: II	HAZCHEM: 2R

## Environmental Care



ONCE OFF conforms with all statutory environmental requirements. It is based on safe ingredients selected so there is no waste or damage. ONCE OFF is biodegradable, non-flammable and chlorine-free. It contains no VOC's (Volatile Organic Compounds) or solvents. Containers will be cleaned and reused if returned to Agar Cleaning Systems significantly reducing plastic usage and waste. They can also be recycled.

## Quality

The design, manufacture and supply of all Agar chemical products is controlled by the Agar Quality Management System which is registered and externally audited by SAI Global as complying with the requirements of AS/NZS ISO 9001 "Quality Management Systems – Requirements". First Certified: 30 April 1996 SAI Certificate No.: QEC7358

## Application

- **Caution:** ONCE OFF can be slippery on smooth tiles. Wear rubber boots with safety treads to avoid slipping. Always DILUTE ONCE OFF BEFORE applying it to floors. Do not allow the solution to come into contact with aluminium, brass, floor polish, marble, terrazzo, wood or carpet. If splashed on any of these surfaces, wash it off immediately. Read the Safety Data Sheet before using this product.
- **Heavy Duty Scrubbing and initial cleans:** Dilute 1 part ONCE OFF to 10 parts water. Pour mixture liberally over floor, scrub with a brush or autoscrubber and allow to soak for 10 minutes. Pick up dirty solution and rinse floor.
- **Heavy Duty Cleaning:** 1 part ONCE OFF to 60 parts water. Approximately  $\frac{2}{3}$  cup ONCE OFF in a 10L bucket of water, 1L ONCE OFF in a small autoscrubber, 2L ONCE OFF in a large autoscrubber.
- **Light Duty Cleaning:** 1 part ONCE OFF in a 120 parts water: Approximately  $\frac{1}{3}$  cup ONCE OFF in a 10L Bucket of water,  $\frac{1}{2}$  L ONCE OFF in a small autoscrubber, 1L ONCE OFF in a large autoscrubber.
- **NOTE:** When autoscrubbing, ensure plenty of diluted solution is laid by the autoscrubber to allow satisfactory dissolving and removal of soil from floor. This allows more complete collection of soil by the squeegee and vacuum.
- If using ONCE OFF every day, scrub the floor with only water once per week. This will prevent any accumulation of alkaline residues.
- To speed up the process, ONCE OFF may be applied to the floor at 1 in 20 in water and LEFT TO DISSOLVE THE DIRT for at least 10 minutes. Scrubbing (without squeegee) will assist. After this time, the solution should be picked up by the squeegee and vacuum, with clean water being laid onto the floor.
- When maintaining porous tiles, it is essential to use white nylon brushes on the autoscrubber at least 3 times a week to ensure that the grout lines are kept clean, because soil left in the grout lines will cause soiling on the tiles themselves.

Available in: 5L

Agar Cleaning Systems maintains Safety Data Sheets (SDS) on all of its products. These sheets contain information that you may need to protect your employees and customers against health or safety hazards associated with our product. Agar Cleaning Systems recommends that you obtain a copy of the respective SDS sheet prior to using this product. The information in the Product Data Sheet is based on data we believe to be reliable. It is offered in good faith, but without guarantee, as conditions and methods of use of our product are beyond our control.